

1. A system for dispensing a filament of liquid assisted by pressurized process air, and convertible between two filament dispensing patterns, the system comprising:
- (a) a housing having
 - 5 (i) a liquid supply passage in fluid communication with said liquid outlet of said dispensing valve,
 - (ii) a process air supply passage, and
 - (iii) a recess having a nozzle mounting surface, said liquid supply passage and said process air supply passage opening on said
10 nozzle mounting surface;
 - (b) a first nozzle having an inlet side and an outlet side, said inlet side positioned within said recess and adjacent said mounting surface and said outlet side having at least one liquid discharge orifice and a plurality of process air discharge passages arranged in a first configuration
15 adjacent said liquid discharge orifice, said liquid discharge orifice and said process air discharge passages respectively being in fluid communication with said liquid supply passage and said process air supply passage of said housing; and
 - (d) a second nozzle configured to be substituted for said
20 first nozzle and having an inlet side and an outlet side, said inlet side of said second nozzle positionable within said recess and adjacent said mounting surface and capable of being mounted in sealing engagement with said mounting surface, said outlet side having at least one liquid discharge orifice and a plurality of process air discharge passages arranged in a

25 second configuration differing from said first configuration and positioned
adjacent said liquid discharge orifice of said second nozzle, said liquid
discharge passage and said process air discharge passages of said second
nozzle respectively being in fluid communication with said liquid supply
passage and said process air supply passage when said second nozzle is
30 substituted for said first nozzle and mounted within said recess against said
mounting surface.

2. The apparatus of claim 1, wherein said first and second
nozzles are each selected from a group consisting of a nozzle having liquid
discharge orifices and process air discharge passages configured to produce
meltblown filaments and a nozzle having a liquid discharge orifice and
5 process air discharge passages configured to produce a swirled filament.

3. A nozzle adapted to be coupled to a dispenser having a mounting recess with a first cam surface and a clamping member with a second cam surface, said nozzle configured to dispense a filament of liquid assisted by pressurized process air and comprising:

5 a nozzle body having a top side, a bottom side and a plurality of side walls, said top side including a liquid inlet and a process air inlet, and said bottom side including a liquid discharge orifice in fluid communication with said liquid inlet and a plurality process air discharge passages in fluid communication with said process air inlet, and

10 first and second opposite side walls extending between said top and bottom sides, said first and second opposite side walls each including a cam surface adapted to respectively mate with the first and second cam surfaces of said dispenser.

4. The nozzle of claim 3, further comprising a plurality of liquid discharge orifices in said nozzle body, said liquid discharge orifices and said process air discharge passages configured to produce meltblown filaments.

5. The nozzle of claim 3, further comprising a plurality of liquid discharge orifices in said nozzle body, said liquid discharge orifices and said process air discharge passages configured to produce a swirled filament from each of said liquid discharge orifices.

6. The nozzle of claim 3, wherein said liquid discharge orifice and process air discharge passages are configured to produce a swirled filament.

7. The nozzle of claim 3, further comprising:

an air trough on said top side, said air trough configured to be in fluid communication with said process air inlet and said process air discharge passages of said nozzle, said trough forming a tortuous path for the process air flowing between said top side of said nozzle and said process air discharge passages to reduce the velocity of the process air discharging from said process air discharge passages relative to the velocity of the process air entering said trough.